

Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A method for defining the relationship between frequency and amplitude of a pulse function ~~for acting on a~~ modulating a data stream for transmission in a telecommunications system in accordance with a predetermined modulation scheme to compensate for distortion by a component of the transmitter, ~~the method comprising~~ wherein the telecommunications system has desired criteria for respective associated cost parameters, and the pulse function for modulating is determined by:

~~defining desired cost parameters on the basis of the telecommunications system requirements and the distortion to be compensated for~~ functions representing the deviation of a respective one of the cost parameters from the associated desired system criterion; and

defining the amplitude of the pulse function over a range of frequencies in dependence on the ~~desired cost parameters~~ cost functions and the distortion to be compensated for.

2. (original) A method as claimed in claim 1, wherein the compensation is for non linear distortion.

3. (original) A method as claimed in claim 2, wherein defining the distortion to be compensated for comprises defining first and second distortions.

4. (original) A method as claimed in claim 3, wherein the first and second distortions relate to different component tolerances.

5. (previously presented) A method as claimed in claim 3, wherein the method comprises weighting the first and second distortions.

6. (previously presented) A method as claimed in claim 1, wherein the compensation is for distortion by a linear component of the transmitter.

7. (original) A method as claimed in claim 6, wherein the compensation is for distortion by a reconstruction filter.

8. (previously presented) A method as claimed in claim 2, wherein the compensation is for distortion by a non linear component of the transmitter.

9. (original) A method as claimed in claim 8, wherein the compensation is for distortion by a power amplifier.

10. (currently amended) A method for defining the relationship between frequency and amplitude of a pulse function for acting on a data stream for transmission in a telecommunications system for compensate for distortion by first and second components of the transmitter, the method comprising:

the method of any preceding claim for defining the amplitude of the pulse function over a range of frequencies in dependence on the desired cost parameters for the first component;

defining the cost parameters for the second component on the basis of the distortion to be compensated for the second component; and

defining the amplitude of the pulse function over a range of frequencies in dependence upon the ~~cost parameters~~ distortion functions of the second component and the pulse function defined for the first component.

11. (currently amended) A method as claimed in claim 10, ~~when dependent upon any of claim 6 or 7,~~ wherein the compensation for distortion by the second component is compensation for non linear distortion.

12. (original) A method as claimed in claim 11, wherein the compensation is for distortion by a non linear component of the transmitter.

13. (currently amended) A method according to claim 10, wherein the desired cost parameters are selected from one or more of the group including component

tolerances, power efficiency, spectral efficiency, bit error rate, AFC, ~~Nuquist~~, and energy.

14. (previously presented) A method as claimed in claim 10, wherein desired cost parameters are defined on the basis of TDMA telecommunications system requirements.

15. (previously presented) A method as claimed in claim 10, wherein desired cost parameters are defined on the basis of GSM requirements.

16. (previously presented) A method as claimed in claim 14, wherein the pulse function is defined such that a pulse of Gaussian shape may be transmitted.

17. (previously presented) A method as claimed in claim 1, wherein desired cost parameters are defined on the basis of CDMA requirements.

18. (original) A method as claimed in claim 17, wherein the pulse function is defined such that a pulse of the root raised cosine shape may be transmitted.

19. (previously presented) A method according to claim 10, wherein the amplitude of the pulse function over a range of frequencies is defined in an iterative

process in which the pulse function is altered and the cost parameters determined until an acceptable balance of cost parameters is achieved.

20. (previously presented) A method according to claim 10, wherein the method comprises the step of weighting the respective cost parameters.

21. (original) A method according to claim 20, wherein an acceptable balance between the cost parameters is achieved by optimizing the respective costs with the respective weightings.

22. (currently amended) A method according to claim 21, wherein the optimization is performed using an optimizer computer ~~programme~~program.

23. (currently amended) A pulse function generator ~~for converting~~arranged to convert a data stream in accordance with a pulse function shaped in accordance with the relationship defined by the method of claim 10.

24. (currently amended) A modulator for providing a signal for transmission in a telecommunication system comprising:

means arranged for shaping a data stream in accordance with the pulse function generator of claim 23.

25. (original) A modulator according to claim 24, wherein the means for shaping comprises a look-up table.

26. (previously presented) A transceiver for a communication device comprising a modulator in accordance with claim 24 and a demodulator.

27. (original) A communication device operable in communication system comprising a transceiver according to claim 26.

28. (currently amended) A dual mode communication device operable in a first mode in a TDMA telecommunications system in which a channel is a combination of frequency and timeslot and a second mode in a CDMA telecommunications system, comprising a modulator for modulating a data stream with a carrier signal in accordance with a predetermined modulation scheme in both the first and second modes of operation and a pulse function generator for shaping a data stream in accordance with respective pulse functions responsive to the mode of operation of the ~~radio telephone~~ communication device and distortion by a component of the transmitter.

29. (currently amended) A dual mode communication device operable in a first mode when a first set of cost parameters are desired and in a second mode

when a second set of cost parameters are desired, the ~~radiotelephone~~
communication device comprising:

a first pulse function generator for converting a data stream in
accordance with a pulse function shaped in dependence on the first set of desired
cost parameters;

a second pulse function generator for converting a data stream in
accordance with a pulse function shaped in dependence on the second set of
desired cost parameters; and

means for selecting the pulse function generator in accordance with the
mode of operation of the ~~phone~~communication device;

wherein at least one of the pulse functions is shaped in accordance
with the relationship defined by the method of ~~claim~~claim 1.

30. (original) A communication device as claimed in claim 29, which is
operable at a first data rate in the first mode and a second data rate in the second
mode.

31. (original) A communication device as claimed in claim 29, wherein the
first data rate supports voice applications and the second data rate supports data
applications.

32. (currently amended) A dual mode communication device operable in a first mode when a first set of cost parameters are desired and in a second mode when a second set of cost parameters are desired, the radiotelephone comprising:

a modulator for modulating a data stream with a carrier signal in accordance with a predetermined modulation scheme in both the first and second modes of operation;

a first pulse function generator for shaping a data stream in accordance with a pulse function shaped in dependence on the first set of desired cost parameters and distortion by a component of the transmitter;

a second pulse function generator for shaping a data stream in accordance with a pulse function shaped in dependence on the second set of desired cost parameters and distortion by a component of the transmitter; and

means for selecting the pulse function generator in accordance with the mode of operation of the ~~phone~~communication device.

33. (previously presented) A method for selecting a modulation scheme for a communication system using a predetermined transmitter, the method comprising:

defining a pulse function for a first modulation scheme in accordance with the method as claimed in claim 1;

defining a pulse function for a second modulation scheme for the same desired cost parameters;

determining the resultant cost parameters for each scheme; and

selecting the modulation scheme which gives good resultant cost parameters given the desired ones.

34. – 39. (canceled)